

Safety Data Sheet

25ppm Hydrogen Sulfide, 100ppm Carbon Monoxide, 25% LEL Pentane, 18% VOL Oxygen, 2.5% VOL Carbon Dioxide; balance Nitrogen

Ideal Calibrations, LLC 2750 Oakwood Blvd. Melvindale, MI 48122 (734) 956-0539 http://www.idealcalibrations.com/

Section 1: Product and Company Identification

Ideal Calibrations, LLC 2750 Oakwood Blvd. Melvindale, MI 48122 (734) 956-0539 http://www.idealcalibrations.com/

Product Code: 25ppm Hydrogen Sulfide, 100ppm Carbon Monoxide, 25% LEL Pentane, 18% VOL Oxygen, 2.5% VOL Carbon Dioxide; balance Nitrogen

Part Number: 0017 Synonyms: Recommended Use: Calibration of gas detection devices Usage Restrictions: Do not use if current date is past expiration date on cylinder

Section 2: Hazards Identification



Hazard Classification: Aspiration Hazard (Category 1) Gases Under Pressure Specific target organ toxicity (Single Exposure) (Category 3)

Hazard Statements: Contains gas under pressure; may explode if heated May be fatal if swallowed and enters airways May cause respiratory irritation; Toxic to aquatic life Toxic to aquatic life with long lasting effects.

Precautionary Statements Prevention: Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/ vapors/spray. [In case of inadequate ventilation] wear respiratory protection.

Response:

Do NOT induce vomiting. If swallowed: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor. If inhaled: Remove person to fresh air and keep comfortable for breathing.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Store locked up.

Disposal:

Dispose of contents and/or container in accordance with applicable regulations.

Section 3: Composition/Information on Ingredients

| | | CAS # | Cor | ncentration | | |
|-------------------------------------|---|--------------------|-----------------------------|--|--|--|
| Hydrogen Su | lfide | 7783-06-4 | 0.0 | 025 | | |
| Carbon Mond | oxide | 630-08-0 | 0.0 | 1 | | |
| n-Pentane | | 109-66-0 | 0.3 | 5 | | |
| Oxygen | | 7782-44-7 | 18 | | | |
| Carbon Dioxi | de | 124-38-9 | 2.5 | | | |
| Nitrogen | | 7727-37-9 | 79.1 | 1375 | | |
| | • | mical stance | | Chemical F | amily | Trade Names |
| Hydrogen Sulfide | HYDROGEN Inorganic gases SULFIDE | | ases | HYDROGEN SULFIDE (H2S); DIHYDROGEN MONOSULFIDE; DIHYDROGEN SULFIDE; HYDROSULFURIC ACID; SULFUR DIHYDRIDE; SULFURETED HYDROGEN; SULFUR HYDRIDE; STINK DAMP; SEWER GAS; RCRA U135; UN 1053; H2S | | |
| Carbon Monoxide | e i i e e i i e e i e e e e e e e e e e | | Inorganic ga | ases | CARBON OXIDE; CARBON OXIDE (CO); UN 1016; CO | |
| n-Pentane N-PENTANE | | | Hydrocarbo Aliphatic, Sa | | PENTANE; AMYL HYDRIDE; UN 1265; C5H12 | |
| Oxygen OXYGEN, COMPRESSED GAS | | | Inorganic ga | ases | OXYGEN; DIOXYGEN; MOLECULAR OXYGEN; OXYGEN MOLECULE; PURE OXYGEN; UN 1072; O2 | |
| Carbon Dioxide | CAR GAS | BON DIOXID | E, | Inorganic ga | ases | CARBONIC ACID GAS; CARBONIC ANHYDRIDE; CARBON DIOXIDE; CARBON OXIDE; UN 1013; CO2 |
| Nitrogen | | ROGEN, IPRESSED | | Inorganic ga | ases | DIATOMIC NITROGEN; DINITROGEN; NITROGEN; NITROGEN-14; NITROGEN GAS; UN 1066; N2 |

Section 4: First Aid Measures

| | Skin Contact | Eye Contact | Ingestion | Inhalation | Note to Physicians |
|---------------------|---|--|--|---|---|
| Hydrogen Sulfide | Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse. | Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention. | If a large amount is swallowed, get medical attention. | If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention. | For inhalation, consider oxygen. |

| | Skin Contact | Eye Contact | Ingestion | Inhalation | Note to Physicians |
|--------------------|---|---|--|---|---|
| Carbon Monoxide | Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse. | Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention. | If a large amount is swallowed, get medical attention. | If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention. | For inhalation, consider oxygen. |
| n-Pentane | Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. | ninutes plenty of water for at NOT induce vomiting. If remove to uncontaminated | | Not available | |
| Oxygen | None expected | None expected | Not likely route of exposure | If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. Get immediate medical attention. | None |
| Carbon Dioxide | If frostbite or freezing occur, immediately flush with plenty of lukewarm water (105-115 F; 41-46 C). DO NOT USE HOT WATER. If warm water is not available, gently wrap affected parts in blankets. Get immediate medical attention. | Contact with liquid: Immediately flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention. | Do not induce vomiting. | If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention. | For inhalation, consider oxygen. |
| Nitrogen | Wash exposed skin with soap and water. | Flush eyes with plenty of water. | If a large amount is swallowed, get medical attention. | If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention. | For inhalation, consider oxygen. |

Section 5: Fire Fighting Measures

| | Suitable Extinguishing Media | Products of Combustion | Protection of Firefighters |
|---------------------|--|---|--|
| Hydrogen Sulfide | Let burn unless leak can be stopped immediately. Large fires: Use regular foam or flood with fine water spray. | Sulfur oxides | Any self-contained breathing apparatus with a full facepiece. Protective material types: butyl rubber, polyvinyl chloride (PVC), neoprene |
| Carbon Monoxide | Carbon dioxide, regular dry chemical Large fires: Use regular foam or flood with fine water spray. | Carbon dioxide | Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. |
| n-Pentane | Regular dry chemical, carbon dioxide, water, regular foam Large fires: Use regular foam or flood with fine water spray. | Carbon monoxide, carbon dioxide and toxic and irritating fumes | Any self-contained breathing apparatus with a full facepiece. Any self-contained breathing apparatus with a full facepiece. |
| Oxygen | Non-flammable. Use extinguishing agent appropriate for the material which is burning. Use water in large quantities for fires involving oxygen. | Oxides of burning material | Respiratory protection may be needed for frequent or heavy exposure. None |

| | Suitable Extinguishing Media | Products of Combustion | Protection of Firefighters |
|-------------------|--|---------------------------|---|
| Carbon Dioxide | Non-flammable | Non-flammable | Any appropriate escape-type, self-contained breathing apparatus. Non-flammable |
| Nitrogen | Non-flammable. Use suitable extinguishing media for surrounding fire. Cylinders may rupture or explode if exposed to heat. | Non-flammable | Respiratory protection may be needed for frequent or heavy exposure. |

Section 6: Accidental Release Measures

| | Personal Precautions | Environmental Precautions | Methods for Containment |
|---------------------|---|---|---|
| Hydrogen Sulfide | Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas. Ventilate closed spaces before entering. Evacuation radius: 150 feet. For tank, rail car or tank truck: 800 meters (1/2 mile). Do not touch spilled material. | Avoid heat, flames, sparks and other sources of ignition. | Stop leak if possible without personal risk. Remove sources of ignition. Reduce vapors with water spray. Do not get water directly on material. |
| Carbon Monoxide | Keep unnecessary people away, isolate hazard area and deny entry. Ventilate closed spaces before entering. | Avoid heat, flames, sparks and other sources of ignition. Keep out of water supplies and sewers. | Stop leak if possible without personal risk. Reduce vapors with water spray. Remove sources of ignition. |
| n-Pentane | Keep unnecessary people away, isolate hazard area and deny entry. | Avoid heat, flames, sparks and other sources of ignition. | Stop leak if possible without personal risk. Reduce vapors with water spray. Remove sources of ignition. |
| Oxygen | Keep unnecessary people away, isolate hazard area and deny entry. Ventilate closed spaces before entering. | Avoid contact with combustible materials. | Stop leak if possible without personal risk. |
| Carbon Dioxide | Keep unnecessary people away, isolate hazard area and deny entry. Ventilate closed spaces before entering. Do not touch spilled material. | Subject to California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65). Keep out of water supplies and sewers. | Stop leak if possible without personal risk. |
| Nitrogen | Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas. | No significant effects from contamination expected. | Stop leak if possible without personal risk. |

| | Methods for Cleanup | Other Information |
|---------------------|---|--|
| Hydrogen Sulfide | Collect runoff for disposal as potential hazardous waste. Dike for later disposal. Absorb with sand or other non-combustible material. Add an alkaline material (lime, crushed limestone, sodium bicarbonate, or soda ash). | Notify Local Emergency Planning Committee and State Emergency Response Commission for release greater than or equal to RQ (U.S. SARA Section 304). If release occurs in the U.S. and is reportable under CERCLA Section 103, notify the National Response Center at (800)424- 8802 (USA) or (202)426-2675 (USA). |
| Carbon Monoxide | Stop leak, evacuate area. Wear protective equipment. | Subject to California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65). |
| n-Pentane | Small spills: Absorb with sand or other non- combustible material. Collect spilled material in appropriate container for disposal. Large spills: Dike for later disposal. | Not available |
| Oxygen | Stop leak and ventilate | None |
| Carbon Dioxide | Stop leak, evacuate, remove source of ignition. | None |
| Nitrogen | N/A | N/A |

Section 7: Handling and Storage

Handling

Storage

| | Handling | Storage |
|---------------------|---|--|
| Hydrogen Sulfide | Store and handle in accordance with all current regulations and standards. Protect from physical damage. Store outside or in a detached building. Store in a cool, dry place. Store in a well-ventilated area. Avoid contact with light. Grounding and bonding required. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101. Notify State Emergency Response Commission for storage or use at amounts greater than or equal to the TPQ (U.S. EPA SARA Section 302). SARA Section 303 requires facilities storing a material with a TPQ to participate in local emergency response planning (U.S. EPA 40 CFR 355.30). Keep separated from incompatible substances. | Subject to handling regulations: U.S. OSHA 29 CFR 1910.119. |
| Carbon Monoxide | Keep separated from incompatible substances. | Store and handle in accordance with all current regulations and standards. Grounding and bonding required. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101. |
| n-Pentane | Store and use with adequate ventilation. Firmly secure cylinders upright to keep them from falling or being knocked over. Screw valve protection cap firmly in place by hand. Store only where temperature will not exceed 125F (52C). Store full and empty cylinders separately. Use a first-in, first-out inventory system to prevent storing full cylinders for long periods. | Do not get liquid in eyes, on skin, or clothing. Protect cylinders from damage. Use a suitable hand truck to move cylinders; do not drag, roll, slide, or drop. Open valve slowly. Close cylinder valve after each use; keep closed even when empty. If valve is hard to open, discontinue use and contact your supplier. |
| Oxygen | Store and handle in accordance with all current regulations and standards. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101. | Keep separated from incompatible substances. |
| Carbon Dioxide | Subject to storage regulations: U.S. OSHA 29 CFR 1910.101. Keep separated from incompatible substances. | Store and handle in accordance with all current regulations and standards |
| Nitrogen | Store and handle in accordance with all current regulations and standards. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101. | Keep separated from incompatible substances. |

Section 8: Exposure Controls/Personal Protection

| | Exposure Guidelines |
|---------------------|---|
| Hydrogen Sulfide | HYDROGEN SULFIDE: 20 ppm OSHA ceiling 50 ppm OSHA peak 10 minute(s) (once if no other measurable exposure occurs) 10 ppm (14 mg/m3) OSHA TWA (vacated by 58 FR 35338, June 30, 1993) 15 ppm (21 mg/m3) OSHA STEL (vacated by 58 FR 35338, June 30, 1993) 10 ppm ACGIH TWA 15 ppm ACGIH STEL 10 ppm (15 mg/m3) NIOSH recommended ceiling 10 minute(s) TLV-TWA: 1ppm Upper respiratory irritation (ACGIH) |
| Carbon | CARBON MONOXIDE: 50 ppm (55 mg/m3) OSHA TWA 35 ppm (40 mg/m3) OSHA TWA (vacated by 58 FR 35338, June 30, |
| Monoxide | 1993) 200 ppm (229 mg/m3) OSHA ceiling (vacated by 58 FR 35338, June 30, 1993) 25 ppm ACGIH TWA 35 ppm (40 mg/m3) NIOSH recommended TWA 10 hour(s) 200 ppm (229 mg/m3) NIOSH recommended ceiling |
| n-Pentane | PENTANE: 1000 ppm (2950 mg/m3) OSHA TWA 600 ppm (1770 mg/m3) OSHA TWA (vacated by 58 FR 35338, June 30, 1993) 750 ppm (2210 mg/m3) OSHA STEL (vacated by 58 FR 35338, June 30, 1993) 600 ppm ACGIH TWA 120 ppm (350 mg/m3) NIOSH recommended TWA 10 hour(s) 610 ppm (1800 mg/m3) NIOSH recommended ceiling 15 minute(s) |
| Oxygen | OXYGEN, COMPRESSED GAS: No occupational exposure limits established. |
| Carbon Dioxide | CARBON DIOXIDE, GAS: CARBON DIOXIDE: 5000 ppm (9000 mg/m3) OSHA TWA 10000 ppm (18000 mg/m3) OSHA TWA (vacated by 58 FR 35338, June 30, 1993) 30000 ppm (54000 mg/m3) OSHA STEL (vacated by 58 FR 35338, June 30, 1993) 5000 ppm ACGIH TWA 30000 ppm ACGIH STEL 5000 ppm (9000 mg/m3) NIOSH recommended TWA 10 hour(s) 30000 ppm (54000 mg/m3) NIOSH recommended STEL |
| Nitrogen | NITROGEN, COMPRESSED GAS: NITROGEN: ACGIH (simple asphyxiant) |

Engineering Controls Handle only in fully enclosed systems.

| | Eye Protection | Skin Protection | Respiratory Protection |
|---------------------|---|---|--|
| Hydrogen Sulfide | Wear splash resistant safety goggles with a face shield. Provide an emergency eye wash fountain and quick drench shower in the immediate work area. | Wear appropriate chemical resistant clothing. | Any self-contained breathing apparatus with a full facepiece. |
| Carbon Monoxide | Eye protection not required, but recommended. | Protective clothing is not required. | Any supplied-air respirator with full facepiece and operated in a pressure- demand or other positive-pressure mode in combination with a separate escape supply. |
| n-Pentane | Wear splash resistant safety goggles. Provide an emergency eye wash fountain and quick drench shower in the immediate work area. | Wear appropriate chemical resistant clothing. | Any self-contained breathing apparatus with a full facepiece. |
| Oxygen | Eye protection not required, but recommended. | Protective clothing is not required. | Respiratory protection may be needed for frequent or heavy exposure. |

| | Eye Protection | Skin Protection | Respiratory Protection |
|-------------------|--|--|--|
| Carbon Dioxide | For the gas: Eye protection not required, but recommended. For the liquid: Wear splash resistant safety goggles. Contact lenses should not be worn. Provide an emergency eye wash fountain and quick drench shower in the immediate work area. | For the gas: Protective clothing is not required. For the liquid: Wear appropriate protective, cold insulating clothing. | Any appropriate escape-type, self- contained breathing apparatus. |
| Nitrogen | Eye protection not required, but recommended. | Protective clothing is not required. | Respiratory protection may be needed for frequent or heavy exposure. |

General Hygiene considerations

- Avoid breathing vapor or mist
- Avoid contact with eyes and skin
- Wash thoroughly after handling and before eating or drinking

Section 9: Physical and Chemical Properties

| | Physical State | Appearance | Color | Change in Appearance | Physical Form | Odor | Taste |
|------------------|----------------|------------|-----------|----------------------|---------------|-----------------|------------|
| Hydrogen Sulfide | Gas | Colorless | Colorless | N/A | Gas | Rotten egg odor | N/A |
| Carbon Monoxide | Gas | Colorless | Colorless | N/A | Gas | Odorless | Tasteless |
| n-Pentane | Liquid | Clear | Colorless | N/A | Liquid | Gasoline odor | N/A |
| Oxygen | Gas | Clear | Colorless | N/A | Gas | Odorless | Tasteless |
| Carbon Dioxide | Gas | Colorless | Colorless | N/A | Gas | Odorless | Acid taste |
| Nitrogen | Gas | Clear | Colorless | N/A | Gas | Odorless | Tasteless |

| | Flash Point | Flammability | Partition Coefficient | Autoignition Temperature | Upper Explosive Limits | Lower Explosive Limits |
|---------------------|-------------------------|---------------|--|-----------------------------|---------------------------|---------------------------|
| Hydrogen Sulfide | Flammable | Not available | Not available | 500 F (260 C) | 45.5% | 3.9% |
| Carbon Monoxide | Flammable | Not available | 1479.11 (log = 3.17) (estimated from water solubility) | 1128-1202 F (609- 650 C) | 0.74 | 12.0-12.5% |
| n-Pentane | <-40 F (<-40 C) (CC) | IA | Not available | 500 F (260 C) | 0.078 | 0.014 |
| Oxygen | Not flammable | Not available | Not available | Nonflammable | Nonflammable | Nonflammable |
| Carbon Dioxide | Not flammable | Not available | N/A | Nonflammable | Nonflammable | Nonflammable |
| Nitrogen | Not flammable | Not available | Not available | Nonflammable | Nonflammable | Nonflammable |

| | Boiling Point | Freezing Point | Vapor Pressure | Vapor Density | Specific Gravity | Water Solubility | рН | Odor Threshold | Evaporation Rate | Viscosity |
|---------------------|---|-------------------------------------|---|------------------|---------------------|---------------------|---|-------------------|------------------------|-------------------------|
| Hydrogen Sulfide | -78 to - 77 F (- 61 to - 60.3 C) | -123 F (- 86 C) | 15200 mmHg @ 25 C | 1.2 (Air=1) | 1.192 | 2.58-2.9% @ 20 C | 4.5-<7 (saturated solution) | 0.13 ppm | Not applicable | 0.0128 cP @ 25 C |
| Carbon Monoxide | -312.7 F (-191.5 C) | -326 F (- 199 C) | 760 mmHg @ -191 C gas; cannot be liquefied at room temperature | 0.968 (Air=1) | Not applicable | 2.3% @ 20 C | Not applicable | Not available | Not applicable | 0.01657 cP @ 0 C |
| n- Pentane | 96.93 F (36.07 C) | -201.5 F (-129.7 C) | 400 mmHg @ 18.5 C | 2.5 (Air=1) | 0.626 | 0.0004 | Not available | 2.2-5000 ppm | 28.6 (butyl acetate=1) | <32 SUS |
| Oxygen | -297 F (- 183 C) | -360 F (- 218 C) | 760 mmHg @ -183 C | 1.1 (Air=1) | Not applicable | 3.2% @ 25 C | Not applicable | Not available | Not applicable | 0.02075 cP @ 25 C |
| Carbon Dioxide | Not available | -71 F (- 57 C) @ 4000 mmHg | 43700 mmHg @ 21 C | 1.5 (Air=1) | 1.522 @ 21 C | Soluble | 3.7 (saturated aqueous solution) @ 101.3 kPa (carbonic acid) | Not available | Not applicable | 0.01657 cP @ 0 C |

| | Boiling Point | Freezing Point | Vapor Pressure | Vapor Density | Specific Gravity | Water Solubility | рН | Odor Threshold | Evaporation Rate | Viscosity |
|----------|---------------------|---------------------|----------------------|------------------|---------------------|---------------------|-------------------|-------------------|---------------------|-------------------------|
| Nitrogen | -321 F (- 196 C) | -346 F (- 210 C) | 760 mmHg @ -196 C | 0.967 (Air=1) | Not applicable | 1.6% @ 20 C | Not applicable | Not available | Not applicable | 0.01787 cP @ 27 C |

| | Molecular Weight | Molecular Formula | Density | Weight per Gallon | Volatility by Volume | Volatility | Solvent Solubility |
|---------------------|---------------------|----------------------|---------------------|----------------------|-------------------------|-------------------|---|
| Hydrogen Sulfide | 34.08 | H2-S | 1.539 g/L @ 0 C | Not available | Not available | Not applicable | Soluble: Carbon disulfide, alcohol, ether, glycerol, gasolines, kerosene, crude oil, alkali solutions |
| Carbon Monoxide | 28.01 | C-0 | 1.250 g/L @ 0 C | Not available | 100% | Not applicable | Soluble: Alcohol, benzene, acetic acid, ethyl acetate, chloroform, cuprous chloride solutions |
| n-Pentane | 72.15g/mol | C5-H12 | Not available | Not available | Not available | Not available | Soluble: Alcohol, ether, acetone, benzene, chloroform |
| Oxygen | 31.9988 | 02 | 1.309 g/L @ 25 C | Not available | Not applicable | Not applicable | Soluble: Alcohol |
| Carbon Dioxide | 44.01 | C-O2 | 0.114 | Not available | Not applicable | Not applicable | Soluble: Alcohol, acetone, hydrocarbons, organic solvents |
| Nitrogen | 28.0134 | N2 | 1.2506 g/L | Not available | 100% | 1 | Soluble: Liquid ammonia |

Section 10: Stability and Reactivity

| | Stability | Conditions to Avoid | Incompatible Materials |
|---------------------|---|---|---|
| Hydrogen Sulfide | Stable at normal temperatures and pressure. | Stable at normal temperatures and pressure. | Combustible materials, metals, oxidizing materials, halogens, metal oxides, metal salts, bases, rust, oxidants, oxygen, copper powder, acetaldehyde, silver fulminate |
| Carbon Monoxide | Stable at normal temperatures and pressure. | Stable at normal temperatures and pressure. | Oxidizing materials, halogens, metal oxides, metals, combustible materials, lithium |
| n-Pentane | Stable at normal temperatures and pressure. | Stable at normal temperatures and pressure. | Oxidizing materials, combustible materials, halogen compounds |
| Oxygen | Stable at normal temperatures and pressure. | Stable at normal temperatures and pressure. | Combustible materials, halo carbons, metals, bases, reducing agents, amines, metal salts, oxidizing materials, alkaline earth and alkali metals |
| Carbon Dioxide | Stable at normal temperatures and pressure. | Stable at normal temperatures and pressure. | Combustible materials, oxidizing materials, metal salts, reducing agents, metal carbide, metals, bases |
| Nitrogen | Stable at normal temperatures and pressure. | Stable at normal temperatures and pressure. | Metals, oxidizing materials |

| | Hazardous Decomposition Products | Possibility of Hazardous Reactions |
|------------------|--------------------------------------|------------------------------------|
| Hydrogen Sulfide | Oxides of sulfur | Will not polymerize. |
| Carbon Monoxide | Oxides of carbon | Will not polymerize. |
| n-Pentane | Oxides of carbon | Will not polymerize. |
| Oxygen | Miscellaneous decomposition products | Will not polymerize. |
| Carbon Dioxide | Carbon monoxide | Will not polymerize. |
| Nitrogen | Oxides of nitrogen | Will not polymerize. |

Section 11: Toxicology Information

Acute Effects

| | Oral LD50 | Dermal LD50 | Inhalation |
|---------------------|-----------------------------------|--|---|
| Hydrogen Sulfide | 444 ppm inhalation-rat LC50 | Irritation 0.000125 ppm/5 hour(s) eyes-human | Irritation, lack of sense of smell, sensitivity to light, nausea, vomiting, difficulty breathing, headache, drowsiness, dizziness, disorientation, tremors, visual disturbances, suffocation, lung congestion, internal bleeding, heart damage, nerve damage, brain damage, coma, death |

| | Oral LD50 | Dermal LD50 | Inhalation |
|--------------------|---|-----------------|---|
| Carbon Monoxide | LC50 Inhalation Gas. Rat 1807 ppm 4 hours | Not available | Changes in body temperature, changes in blood pressure, nausea, vomiting, chest pain, difficulty breathing, irregular heartbeat, headache, drowsiness, dizziness, disorientation, hallucinations, pain in extremities, tremors, loss of coordination, hearing loss, visual disturbances, eye damage, suffocation, blood disorders, convulsions, coma |
| n-Pentane | >2000 mg/kg oral- rat LD50 | Not available | Irritation, nausea, difficulty breathing, headache, drowsiness, dizziness, disorientation, mood swings, loss of coordination, central nervous system depression, asphyxiant |
| Oxygen | Not established | Not established | Irritation, changes in body temperature, nausea, difficulty breathing, irregular heartbeat, dizziness, disorientation, hallucinations, mood swings, pain in extremities, tremors, lung congestion, convulsions |
| Carbon Dioxide | Not established | Not established | Ringing in the ears, nausea, irregular heartbeat, headache, drowsiness, dizziness, tingling sensation, visual disturbances, suffocation, convulsions, coma |
| Nitrogen | Not available | Not available | Nausea, vomiting, difficulty breathing, headache, drowsiness, dizziness, tingling sensation, loss of coordination, convulsions, coma |

| | Eye Irritation | Skin Irritation | Sensitization |
|---------------------|---|---|---|
| Hydrogen Sulfide | Irritation, sensitivity to light, visual disturbances | Irritation liquid: frostbite | Acute toxicity, Category 2, inhalation; H330: Fatal if inhaled. Specific Target Organ Toxicity (single exposure), Category 3; H335: May cause respiratory irritation. Hazardous to the aquatic environment, Acute Category 1; H400: Very toxic to aquatic life |
| Carbon Monoxide | No information on significant adverse effects | No information on significant adverse effects | Acute toxicity, Category 3, inhalation; H331: Toxic if inhaled. Reproductive toxicity, Category 1A; H360D: May damage the unborn child. Specific Target Organ Toxicity (repeated exposure), Category 1; H372: Causes damage to organs through prolonged or repeated exposure. |
| n-Pentane | Irritation | Irritation | Specific Target Organ Toxicity (single exposure), Category 3; H336: May cause drowsiness or dizziness. Aspiration hazard, Category 1; H304: May be fatal if swallowed and enters airways. |
| Oxygen | No information on significant adverse effects | No information on significant adverse effects | No significant target effects reported. |
| Carbon Dioxide | Irritation, frostbite, blurred vision | Liquid: blisters, frostbite | Difficulty breathing |
| Nitrogen | Contact with rapidly expanding gas may cause burns or frostbite | No information on significant adverse effects | Difficulty breathing |

Chronic Effects

| | Carcinogenicity | Mutagenicity | Reproductive Effects | Developmental Effects |
|------------------|-----------------|-----------------|----------------------|------------------------------|
| Hydrogen Sulfide | Not available | Not available | Available. | No data |
| Carbon Monoxide | Not available | Available. | Available. | No data |
| n-Pentane | Not available | Not available | Not available | No data |
| Oxygen | Not known. | Available. | Available. | No data |
| Carbon Dioxide | Not available | Not established | Available. | No data |
| Nitrogen | Not hazardous | Not available | Not available | No data |

Section 12: Ecological Information

Fate and Transport

| | Eco toxicity | Persistence / Degradability | Bioaccumulation / Accumulation | Mobility in Environment |
|---------------------|--|--|-----------------------------------|---|
| Hydrogen Sulfide | Fish toxicity: Acute LC50 7 ug/L Fresh water Fish - Fathead minnow - Pimephales promelas - FRY 96 hours; 14.9 ug/L 96 hour(s) LC50 (Mortality) Fathead minnow (Pimeph Invertibrate toxicity: 9730 ug/L 1.5 hour(s) (Mortality) Mediterranean mussel (Mytilus galloprovincialis) Algal toxicity: Not available Phyto toxicity: Not available Other toxicity: Not available | Highly toxic to aquatic life. | Not available | Not available |
| Carbon Monoxide | Fish toxicity: 75000 ug/L 1 day(s) LC100 (Mortality) Orangespotted sunfish (Lepomis humilis) Invertibrate toxicity: Not available Algal toxicity: Not available | Relatively non-persistent in the environment. Highly volatile from water. | Not available | Not expected to leach through the soil or the sediment. |

| | Phyto toxicity: Not available Other toxicity: Not available | | | |
|-------------------|---|--|--|--------------------------|
| n-Pentane | Fish toxicity: Not available Invertibrate toxicity: 3000000 ug/L 48 week(s) (Mortality) Pacific oyster (Crassostrea gigas) Algal toxicity: 1000 ug/L 8 year(s) EC50 (Photosynthesis) Algae,phytoplankton,algal mat (Algae) Phyto toxicity: Not available Other toxicity: Not available | Not available | Not available | Not available |
| Oxygen | Fish toxicity: Not available Invertibrate toxicity: Not available Algal toxicity: Not available Phyto toxicity: Not available Other toxicity: Not available | Not available | Low bioaccumulation | Not available |
| Carbon Dioxide | Fish toxicity: 150000 ug/L 48 day(s) (Mortality) Brown trout (Salmo trutta) Invertibrate toxicity: Not available Algal toxicity: Not available Phyto toxicity: Not available Other toxicity: Not available | Relatively non-persistent in the environment. Moderately volatile from water. | Accumulates very little in the bodies of living organisms. | Leaches through the soil |
| Nitrogen | Fish toxicity: Not available Invertibrate toxicity: Not available Algal toxicity: Not available Phyto toxicity: Not available Other toxicity: Not available | Not available | Not available | Not available |

Section 13: Disposal Considerations

| Hydrogen Sulfide | Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): U135. |
|---------------------|---|
| Carbon Monoxide | Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): D001. |
| n-Pentane | Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): D001. |
| Oxygen | Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): D001. |
| Carbon Dioxide | Dispose in accordance with all applicable regulations. |
| Nitrogen | Dispose in accordance with all applicable regulations. |

Section 14: Transportation Information

U.S. DOT 49 CFR 172.101

DOT Information For This Mixture

| Shipping Name | Compressed gas, n.o.s. (Nitrogen, Oxygen) | | | |
|--------------------|---|--|--|--|
| UN Number | UN1956 | | | |
| Hazard Class | 2.2 | | | |
| Hazard Information | Non-Flammable Gas | | | |
| | | | | |
| | | | | |

Individual Component Information

| | Proper Shipping Name | ID Number | Hazard Class or Division | Packing Group | Labeling Requirements | Passenger Aircraft or Railcar Quantity Limitations | Cargo Aircraft Only Quantity Limitations | Additional Shipping Description |
|---------------------|----------------------------|--------------|--------------------------------|-------------------|--------------------------|---|--|---------------------------------------|
| Hydrogen Sulfide | Hydrogen sulfide | UN1053 | 2.3 | Not applicable | 2.3; 2.1 | Forbidden | Forbidden | Toxic- Inhalation Hazard Zone B |

| | Proper Shipping Name | ID Number | Hazard Class or Division | Packing Group | Labeling Requirements | Passenger Aircraft or Railcar Quantity Limitations | Cargo Aircraft Only Quantity Limitations | Additional Shipping Description |
|--------------------|-----------------------------------|--------------|--------------------------------|-------------------|--------------------------|---|--|---------------------------------------|
| Carbon Monoxide | Carbon monoxide, compressed | UN1016 | 2.3 | Not applicable | 2.3; 2.1 | Forbidden | 25 kg | Toxic- Inhalation Hazard Zone D |
| n-Pentane | Pentanes | UN1265 | 3 | 11 | 3 | N/A | N/A | N/A |
| Oxygen | Oxygen, compressed | UN1072 | 2.2 | Not available | 2.2; 5.1 | 75 kg or L | 150 kg | N/A |
| Carbon Dioxide | Carbon dioxide | UN1013 | 2.2 | Not applicable | 2.2 | 75 kg or L | 150kg | None |
| Nitrogen | Nitrogen, compressed | UN1066 | 2.2 | Not applicable | 2.2 | 75 kg or L | 150 kg | N/A |

Canadian Transportation of Dangerous Goods

| | Shipping Name | UN Number | Class | Packing Group / Risk Group |
|---|--|-----------|----------|----------------------------|
| Hydrogen Sulfide | HYDROGEN SULFIDE; or HYDROGEN SULPHIDE | UN1053 | 2.3; 2.1 | Not applicable |
| Carbon Monoxide Carbon monoxide, compressed | | UN1016 | 2.3; 2.1 | Not applicable |
| n-Pentane | Pentanes | UN1265 | 3 | II |
| Oxygen | Oxygen, compressed | UN1072 | 2.2; 5.1 | Not applicable |
| Carbon Dioxide | Carbon dioxide | UN1013 | 2.2 | Not applicable |
| Nitrogen | Nitrogen, compressed | UN1066 | 2.2 | Not applicable |

Section 15: Regulatory Information

U.S. Regulations

| | CERCLA Sections | SARA 355.30 | SARA 355.40 |
|------------------|-----------------|----------------|----------------|
| Hydrogen Sulfide | 100 LBS RQ | 500 LBS TPQ | 100 LBS RQ |
| Carbon Monoxide | Not regulated. | Not regulated. | Not regulated. |
| n-Pentane | Not regulated. | Not regulated. | Not regulated. |
| Oxygen | Not regulated. | Not regulated. | Not regulated. |
| Carbon Dioxide | Not regulated. | Not regulated. | Not regulated. |
| Nitrogen | Not regulated. | Not regulated. | Not regulated. |

SARA 370.21

| | Acute | Chronic | Fire | Reactive | Sudden Release |
|------------------|-------|---------|------|----------|----------------|
| Hydrogen Sulfide | Yes | No | Yes | No | Yes |
| Carbon Monoxide | Yes | No | Yes | No | Yes |
| n-Pentane | Yes | No | Yes | No | No |
| Oxygen | No | No | Yes | No | Yes |
| Carbon Dioxide | Yes | No | No | No | Yes |
| Nitrogen | Yes | No | No | No | Yes |

SARA 372.65

| Hydrogen Sulfide | HYDROGEN SULFIDE: Administrative stay issued Aug. 22, 1994 |
|------------------|--|
| Carbon Monoxide | Not regulated. |
| n-Pentane | Not regulated. |
| Oxygen | Not regulated. |
| Carbon Dioxide | Not regulated. |
| Nitrogen | Not regulated. |

OSHA Process Safety

| Hydrogen Sulfide | 1500 LBS TQ | | |
|------------------|----------------|--|--|
| Carbon Monoxide | Not regulated. | | |
| n-Pentane | Not regulated. | | |
| Oxygen | Not regulated. | | |
| Carbon Dioxide | Not regulated. | | |
| Nitrogen | Not regulated. | | |

State Regulations

| | CA Proposition 65 |
|---------------------|--|
| Hydrogen Sulfide | Not regulated. |
| Carbon Monoxide | WARNING: This product can expose you to chemicals including Carbon Monoxide, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. |
| n-Pentane | Not regulated. |
| Oxygen | Not regulated. |
| Carbon Dioxide | Not regulated. |
| Nitrogen | Not regulated. |

Canadian Regulations

| | WHMIS Classification |
|------------------|----------------------|
| Hydrogen Sulfide | A, B1, D1A, D2B. |
| Carbon Monoxide | A, B1, D1A, D2A. |
| n-Pentane | B2 |
| Oxygen | A,C |
| Carbon Dioxide | A |
| Nitrogen | A |

National Inventory Status

| | US Inventory (TSCA) | TSCA 12b Export Notification | Canada Inventory (DSL/NDSL) |
|------------------|----------------------|--|-----------------------------|
| Hydrogen Sulfide | Listed on inventory. | Not listed. | Listed on inventory. |
| Carbon Monoxide | Listed on inventory. | Not listed. | Listed on inventory. |
| n-Pentane | Listed on inventory. | PENTANE CAS NUMBER: 109-66-0 SECTION 4 | Listed on inventory. |
| Oxygen | Listed on inventory. | Not listed. | Not determined. |
| Carbon Dioxide | Listed on inventory. | Not listed. | Listed on inventory. |
| Nitrogen | Listed on inventory. | Not listed. | Listed on inventory. |

Section 16: Other Information

| | NFPA Rating |
|------------------|---|
| Hydrogen Sulfide | HEALTH=4 FIRE=4 REACTIVITY=0 |
| Carbon Monoxide | HEALTH=2 FIRE=4 REACTIVITY=0 |
| n-Pentane | HEALTH=2 FIRE=4 REACTIVITY=0 |
| Oxygen | HEALTH=0 FIRE=0 REACTIVITY=0 SPECIAL=OX |
| Carbon Dioxide | HEALTH=3 FIRE=0 REACTIVITY=0 SPECIAL=SA |
| Nitrogen | HEALTH=0 FIRE=0 REACTIVITY=0 SPECIAL=SA |

0 = minimal hazard, 1 = slight hazard, 2 = moderate hazard, 3 = severe hazard, 4 = extreme hazard