



## Safety Data Sheet

5ppm Sulfur Dioxide, 25% LEL Pentane,  
50ppm Carbon Monoxide, 15% VOL  
Oxygen; balance Nitrogen

**Ideal Calibrations, LLC**  
2750 Oakwood Blvd.  
Melvindale, MI 48122  
(734) 956-0539  
<http://www.idealcalibrations.com/>

### Section 1: Product and Company Identification

**Ideal Calibrations, LLC**  
2750 Oakwood Blvd.  
Melvindale, MI 48122  
(734) 956-0539  
<http://www.idealcalibrations.com/>

Product Code: 5ppm Sulfur Dioxide, 25% LEL Pentane, 50ppm Carbon Monoxide, 15% VOL Oxygen; balance Nitrogen  
Part Number: 0400

**Synonyms:**

**Recommended Use:** Calibration of gas detection devices

**Usage Restrictions:** Do not use if current date is past expiration date on cylinder

### Section 2: Hazards Identification



**Danger**

**Hazard Classification:**

Aspiration Hazard (Category 1)  
Gases Under Pressure  
Specific target organ toxicity (Single Exposure) (Category 3)

**Hazard Statements:**

Contains gas under pressure; may explode if heated  
May be fatal if swallowed and enters airways  
May cause respiratory irritation;  
Toxic to aquatic life with long lasting effects.

**Precautionary Statements**

**Prevention:**

Use only outdoors or in a well-ventilated area.  
Avoid breathing dust/fume/gas/mist/ vapors/spray.  
[In case of inadequate ventilation] wear respiratory protection.

**Response:**

Do NOT induce vomiting.

If swallowed: Rinse mouth. Do NOT induce vomiting.  
 Immediately call a poison center or doctor.  
 If inhaled: Remove person to fresh air and keep comfortable for breathing.

**Storage:**

Store in a well-ventilated place. Keep container tightly closed.  
 Protect from sunlight.  
 Store locked up.

**Disposal:**

Dispose of contents and/or container in accordance with applicable regulations.

## Section 3: Composition/Information on Ingredients

	CAS #	Concentration
<b>Sulfur Dioxide</b>	7446-09-5	0.0005
<b>n-Pentane</b>	109-66-0	0.35
<b>Carbon Monoxide</b>	630-08-0	0.005
<b>Oxygen</b>	7782-44-7	15
<b>Nitrogen</b>	7727-37-9	84.6445

  

	Chemical Substance	Chemical Family	Trade Names
<b>Sulfur Dioxide</b>	SULFUR DIOXIDE	Inorganic gases	SULFUROUS ACID ANHYDRIDE; SULFUROUS OXIDE; SULPHUR DIOXIDE; SULFUROUS ANHYDRIDE; FERMENTICIDE LIQUID; SULFUR DIOXIDE(SO2); SULFUR OXIDE; SULFUR OXIDE(SO2); STCC 4904290; UN 1079; O2S
<b>n-Pentane</b>	N-PENTANE	Hydrocarbons, Aliphatic, Saturated	PENTANE; AMYL HYDRIDE; UN 1265; C5H12
<b>Carbon Monoxide</b>	CARBON MONOXIDE	Inorganic gases	CARBON OXIDE; CARBON OXIDE (CO); UN 1016; CO
<b>Oxygen</b>	OXYGEN, COMPRESSED GAS	Inorganic gases	OXYGEN; DIOXYGEN; MOLECULAR OXYGEN; OXYGEN MOLECULE; PURE OXYGEN; UN 1072; O2
<b>Nitrogen</b>	NITROGEN, COMPRESSED GAS	Inorganic gases	DIATOMIC NITROGEN; DINITROGEN; NITROGEN; NITROGEN-14; NITROGEN GAS; UN 1066; N2

## Section 4: First Aid Measures

	Skin Contact	Eye Contact	Ingestion	Inhalation	Note to Physicians
<b>Sulfur Dioxide</b>	Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get immediate medical attention. Thoroughly clean and dry contaminated clothing before reuse. Destroy contaminated shoes.	Immediately flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.	If a large amount is swallowed, get medical attention.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.	For inhalation, consider oxygen.
<b>n-Pentane</b>	Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes.	Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.	Aspiration hazard. DO NOT induce vomiting. If vomiting occurs, keep head lower than hips to help prevent aspiration. Get immediate medical attention. Give artificial respiration if not breathing.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. Get immediate medical attention.	Not available

	Skin Contact	Eye Contact	Ingestion	Inhalation	Note to Physicians
<b>Carbon Monoxide</b>	Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.	Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.	If a large amount is swallowed, get medical attention.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.	For inhalation, consider oxygen.
<b>Oxygen</b>	None expected	None expected	Not likely route of exposure	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. Get immediate medical attention.	None
<b>Nitrogen</b>	Wash exposed skin with soap and water.	Flush eyes with plenty of water.	If a large amount is swallowed, get medical attention.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.	For inhalation, consider oxygen.

## Section 5: Fire Fighting Measures

	Suitable Extinguishing Media	Products of Combustion	Protection of Firefighters
<b>Sulfur Dioxide</b>	Non-flammable. Use suitable extinguishing media for surrounding fire.	None known	<ul style="list-style-type: none"> <li>▪ Non-flammable</li> <li>▪ Non-flammable</li> </ul>
<b>n-Pentane</b>	Regular dry chemical, carbon dioxide, water, regular foam Large fires: Use regular foam or flood with fine water spray.	Carbon monoxide, carbon dioxide and toxic and irritating fumes	<ul style="list-style-type: none"> <li>▪ Any self-contained breathing apparatus with a full facepiece.</li> <li>▪ Any self-contained breathing apparatus with a full facepiece.</li> </ul>
<b>Carbon Monoxide</b>	Carbon dioxide, regular dry chemical Large fires: Use regular foam or flood with fine water spray.	Carbon dioxide	<ul style="list-style-type: none"> <li>▪ Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply.</li> <li>▪ Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply.</li> </ul>
<b>Oxygen</b>	Non-flammable. Use extinguishing agent appropriate for the material which is burning. Use water in large quantities for fires involving oxygen.	Oxides of burning material	<ul style="list-style-type: none"> <li>▪ Respiratory protection may be needed for frequent or heavy exposure.</li> <li>▪ None</li> </ul>
<b>Nitrogen</b>	Non-flammable. Use suitable extinguishing media for surrounding fire. Cylinders may rupture or explode if exposed to heat.	Non-flammable	<ul style="list-style-type: none"> <li>▪ Respiratory protection may be needed for frequent or heavy exposure.</li> </ul>

## Section 6: Accidental Release Measures

	Personal Precautions	Environmental Precautions	Methods for Containment
<b>Sulfur Dioxide</b>	Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas. Ventilate closed spaces before entering. Evacuation radius: 150 feet.	Avoid contamination of environment.	Stop leak if possible without personal risk. Reduce vapors with water spray. Do not get water directly on material.
<b>n-Pentane</b>	Keep unnecessary people away, isolate hazard area and deny entry.	Avoid heat, flames, sparks and other sources of ignition.	Stop leak if possible without personal risk. Reduce vapors with water spray. Remove sources of ignition.
<b>Carbon Monoxide</b>	Keep unnecessary people away, isolate hazard area and deny entry. Ventilate closed spaces before entering.	Avoid heat, flames, sparks and other sources of ignition. Keep out of water supplies and sewers.	Stop leak if possible without personal risk. Reduce vapors with water spray. Remove sources of ignition.

	Personal Precautions	Environmental Precautions	Methods for Containment
<b>Oxygen</b>	Keep unnecessary people away, isolate hazard area and deny entry. Ventilate closed spaces before entering.	Avoid contact with combustible materials.	Stop leak if possible without personal risk.
<b>Nitrogen</b>	Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas.	No significant effects from contamination expected.	Stop leak if possible without personal risk.

	Methods for Cleanup	Other Information
<b>Sulfur Dioxide</b>	Stop leak, evacuate area. Contact emergency personnel.	Notify Local Emergency Planning Committee and State Emergency Response Commission for release greater than or equal to RQ (U.S. SARA Section 304). If release occurs in the U.S. and is reportable under CERCLA Section 103, notify the National Response Center at (800)424-8802 (USA) or (202)426-2675 (USA).
<b>n-Pentane</b>	Small spills: Absorb with sand or other non-combustible material. Collect spilled material in appropriate container for disposal. Large spills: Dike for later disposal.	Not available
<b>Carbon Monoxide</b>	Stop leak, evacuate area. Wear protective equipment.	Subject to California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65).
<b>Oxygen</b>	Stop leak and ventilate	None
<b>Nitrogen</b>	N/A	N/A

## Section 7: Handling and Storage

	Handling	Storage
<b>Sulfur Dioxide</b>	Store and use with adequate ventilation. Firmly secure cylinders upright to keep them from falling or being knocked over. Screw valve protection cap firmly in place by hand. Store only where temperature will not exceed 125F (52C). Store full and empty cylinders separately. Use a first-in, first-out inventory system to prevent storing full cylinders for long periods.	Do not get liquid in eyes, on skin, or clothing. Protect cylinders from damage. Use a suitable hand truck to move cylinders; do not drag, roll, slide, or drop. Open valve slowly. Close cylinder valve after each use; keep closed even when empty. If valve is hard to open, discontinue use and contact your supplier.
<b>n-Pentane</b>	Store and use with adequate ventilation. Firmly secure cylinders upright to keep them from falling or being knocked over. Screw valve protection cap firmly in place by hand. Store only where temperature will not exceed 125F (52C). Store full and empty cylinders separately. Use a first-in, first-out inventory system to prevent storing full cylinders for long periods.	Do not get liquid in eyes, on skin, or clothing. Protect cylinders from damage. Use a suitable hand truck to move cylinders; do not drag, roll, slide, or drop. Open valve slowly. Close cylinder valve after each use; keep closed even when empty. If valve is hard to open, discontinue use and contact your supplier.
<b>Carbon Monoxide</b>	Keep separated from incompatible substances.	Store and handle in accordance with all current regulations and standards. Grounding and bonding required. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101.
<b>Oxygen</b>	Store and handle in accordance with all current regulations and standards. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101.	Keep separated from incompatible substances.
<b>Nitrogen</b>	Store and handle in accordance with all current regulations and standards. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101.	Keep separated from incompatible substances.

## Section 8: Exposure Controls/Personal Protection

	Exposure Guidelines
<b>Sulfur Dioxide</b>	SULFUR DIOXIDE: 2 ppm (5 mg/m <sup>3</sup> ) OSHA TWA (vacated by 58 FR 35338, June 30, 1993) 5 ppm (13 mg/m <sup>3</sup> ) OSHA STEL (vacated by 58 FR 35338, June 30, 1993) 5 ppm (13 mg/m <sup>3</sup> ) OSHA TWA 2 ppm ACGIH TWA 5 ppm ACGIH STEL 2 ppm (5 mg/m <sup>3</sup> ) NIOSH recommended TWA 10 hour(s) 5 ppm (13 mg/m <sup>3</sup> ) NIOSH recommended STEL
<b>n-Pentane</b>	PENTANE: 1000 ppm (2950 mg/m <sup>3</sup> ) OSHA TWA 600 ppm (1770 mg/m <sup>3</sup> ) OSHA TWA (vacated by 58 FR 35338, June 30, 1993) 750 ppm (2210 mg/m <sup>3</sup> ) OSHA STEL (vacated by 58 FR 35338, June 30, 1993) 600 ppm ACGIH TWA 120 ppm (350 mg/m <sup>3</sup> ) NIOSH recommended TWA 10 hour(s) 610 ppm (1800 mg/m <sup>3</sup> ) NIOSH recommended ceiling 15 minute(s)
<b>Carbon Monoxide</b>	CARBON MONOXIDE: 50 ppm (55 mg/m <sup>3</sup> ) OSHA TWA 35 ppm (40 mg/m <sup>3</sup> ) OSHA TWA (vacated by 58 FR 35338, June 30, 1993) 200 ppm (229 mg/m <sup>3</sup> ) OSHA ceiling (vacated by 58 FR 35338, June 30, 1993) 25 ppm ACGIH TWA 35 ppm (40 mg/m <sup>3</sup> ) NIOSH recommended TWA 10 hour(s) 200 ppm (229 mg/m <sup>3</sup> ) NIOSH recommended ceiling
<b>Oxygen</b>	OXYGEN, COMPRESSED GAS: No occupational exposure limits established.
<b>Nitrogen</b>	NITROGEN, COMPRESSED GAS: NITROGEN: ACGIH (simple asphyxiant)

## Engineering Controls

Handle only in fully enclosed systems.

	Eye Protection	Skin Protection	Respiratory Protection
<b>Sulfur Dioxide</b>	Wear splash resistant safety goggles with a face shield. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.	For the gas: Wear appropriate chemical resistant clothing. For the liquid: Wear appropriate protective, cold insulating clothing.	Non-flammable
<b>n-Pentane</b>	Wear splash resistant safety goggles. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.	Wear appropriate chemical resistant clothing.	Any self-contained breathing apparatus with a full facepiece.
<b>Carbon Monoxide</b>	Eye protection not required, but recommended.	Protective clothing is not required.	Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply.
<b>Oxygen</b>	Eye protection not required, but recommended.	Protective clothing is not required.	Respiratory protection may be needed for frequent or heavy exposure.
<b>Nitrogen</b>	Eye protection not required, but recommended.	Protective clothing is not required.	Respiratory protection may be needed for frequent or heavy exposure.

### General Hygiene considerations

- Avoid breathing vapor or mist
- Avoid contact with eyes and skin
- Wash thoroughly after handling and before eating or drinking

## Section 9: Physical and Chemical Properties

	Physical State	Appearance	Color	Change in Appearance	Physical Form	Odor	Taste
<b>Sulfur Dioxide</b>	Gas	Clear	Colorless	N/A	Gas	Irritating odor	N/A
<b>n-Pentane</b>	Liquid	Clear	Colorless	N/A	Liquid	Gasoline odor	N/A
<b>Carbon Monoxide</b>	Gas	Colorless	Colorless	N/A	Gas	Odorless	Tasteless
<b>Oxygen</b>	Gas	Clear	Colorless	N/A	Gas	Odorless	Tasteless
<b>Nitrogen</b>	Gas	Clear	Colorless	N/A	Gas	Odorless	Tasteless

	Flash Point	Flammability	Partition Coefficient	Autoignition Temperature	Upper Explosive Limits	Lower Explosive Limits
<b>Sulfur Dioxide</b>	Not flammable	Not available	Not available	Nonflammable	Nonflammable	Nonflammable
<b>n-Pentane</b>	<-40 F (<-40 C) (CC)	IA	Not available	500 F (260 C)	0.078	0.014
<b>Carbon Monoxide</b>	Flammable	Not available	1479.11 (log = 3.17) (estimated from water solubility)	1128-1202 F (609-650 C)	0.74	12.0-12.5%
<b>Oxygen</b>	Not flammable	Not available	Not available	Nonflammable	Nonflammable	Nonflammable
<b>Nitrogen</b>	Not flammable	Not available	Not available	Nonflammable	Nonflammable	Nonflammable

	Boiling Point	Freezing Point	Vapor Pressure	Vapor Density	Specific Gravity	Water Solubility	pH	Odor Threshold	Evaporation Rate	Viscosity
<b>Sulfur Dioxide</b>	14 F (-10 C)	-99 F (-73 C)	2432 mmHg @ 20 C	2.26 (Air=1)	1.462 @ -10 C	22.8% @ 0 C	Acidic in solution	3-5 ppm	>1 (butyl acetate=1)	Not available
<b>n-Pentane</b>	96.93 F (36.07 C)	-201.5 F (-129.7 C)	400 mmHg @ 18.5 C	2.5 (Air=1)	0.626	0.0004	Not available	2.2-5000 ppm	28.6 (butyl acetate=1)	<32 SUS
<b>Carbon Monoxide</b>	-312.7 F (-191.5 C)	-326 F (-199 C)	760 mmHg @ -191 C gas; cannot be liquefied at room temperature	0.968 (Air=1)	Not applicable	2.3% @ 20 C	Not applicable	Not available	Not applicable	0.01657 cP @ 0 C
<b>Oxygen</b>	-297 F (-183 C)	-360 F (-218 C)	760 mmHg @ -183 C	1.1 (Air=1)	Not applicable	3.2% @ 25 C	Not applicable	Not available	Not applicable	0.02075 cP @ 25 C

	Boiling Point	Freezing Point	Vapor Pressure	Vapor Density	Specific Gravity	Water Solubility	pH	Odor Threshold	Evaporation Rate	Viscosity
<b>Nitrogen</b>	-321 F (-196 C)	-346 F (-210 C)	760 mmHg @ -196 C	0.967 (Air=1)	Not applicable	1.6% @ 20 C	Not applicable	Not available	Not applicable	0.01787 cP @ 27 C

	Molecular Weight	Molecular Formula	Density	Weight per Gallon	Volatility by Volume	Volatility	Solvent Solubility
<b>Sulfur Dioxide</b>	64.06	S-O2	0.169	Not available	Not available	Not applicable	Soluble: Alcohol, acetic acid, sulfuric acid, ether, chloroform, benzene, sulfuryl chloride, nitrobenzenes, toluene, acetone
<b>n-Pentane</b>	72.15g/mol	C5-H12	Not available	Not available	Not available	Not available	Soluble: Alcohol, ether, acetone, benzene, chloroform
<b>Carbon Monoxide</b>	28.01	C-O	1.250 g/L @ 0 C	Not available	100%	Not applicable	Soluble: Alcohol, benzene, acetic acid, ethyl acetate, chloroform, cuprous chloride solutions
<b>Oxygen</b>	31.9988	O2	1.309 g/L @ 25 C	Not available	Not applicable	Not applicable	Soluble: Alcohol
<b>Nitrogen</b>	28.0134	N2	1.2506 g/L	Not available	100%	1	Soluble: Liquid ammonia

## Section 10: Stability and Reactivity

	Stability	Conditions to Avoid	Incompatible Materials
<b>Sulfur Dioxide</b>	Stable at normal temperatures and pressure.	Stable at normal temperatures and pressure.	Combustible materials, metals, bases, oxidizing materials, halogens, metal carbide, metal oxides, peroxides, reducing agents, potassium, sodium, nitril chloride, acrolein, metal oxides, carbide
<b>n-Pentane</b>	Stable at normal temperatures and pressure.	Stable at normal temperatures and pressure.	Oxidizing materials, combustible materials, halogen compounds
<b>Carbon Monoxide</b>	Stable at normal temperatures and pressure.	Stable at normal temperatures and pressure.	Oxidizing materials, halogens, metal oxides, metals, combustible materials, lithium
<b>Oxygen</b>	Stable at normal temperatures and pressure.	Stable at normal temperatures and pressure.	Combustible materials, halo carbons, metals, bases, reducing agents, amines, metal salts, oxidizing materials, alkaline earth and alkali metals
<b>Nitrogen</b>	Stable at normal temperatures and pressure.	Stable at normal temperatures and pressure.	Metals, oxidizing materials

	Hazardous Decomposition Products	Possibility of Hazardous Reactions
<b>Sulfur Dioxide</b>	Forms sulfurous acid solution on reaction with water.	Will not polymerize.
<b>n-Pentane</b>	Oxides of carbon	Will not polymerize.
<b>Carbon Monoxide</b>	Oxides of carbon	Will not polymerize.
<b>Oxygen</b>	Miscellaneous decomposition products	Will not polymerize.
<b>Nitrogen</b>	Oxides of nitrogen	Will not polymerize.

## Section 11: Toxicology Information

### Acute Effects

	Oral LD50	Dermal LD50	Inhalation
<b>Sulfur Dioxide</b>	LC50, 1 hr, rat = 2520 ppm	Not available	Allergic reactions, burns, toxic
<b>n-Pentane</b>	>2000 mg/kg oral-rat LD50	Not available	Irritation, nausea, difficulty breathing, headache, drowsiness, dizziness, disorientation, mood swings, loss of coordination, central nervous system depression, asphyxiant
<b>Carbon Monoxide</b>	LC50 Inhalation Gas. Rat 1807 ppm 4 hours	Not available	Changes in body temperature, changes in blood pressure, nausea, vomiting, chest pain, difficulty breathing, irregular heartbeat, headache, drowsiness, dizziness, disorientation, hallucinations, pain in extremities, tremors, loss of coordination, hearing loss, visual disturbances, eye damage, suffocation, blood disorders, convulsions, coma

	Oral LD50	Dermal LD50	Inhalation
<b>Oxygen</b>	Not established	Not established	Irritation, changes in body temperature, nausea, difficulty breathing, irregular heartbeat, dizziness, disorientation, hallucinations, mood swings, pain in extremities, tremors, lung congestion, convulsions
<b>Nitrogen</b>	Not available	Not available	Nausea, vomiting, difficulty breathing, headache, drowsiness, dizziness, tingling sensation, loss of coordination, convulsions, coma

	Eye Irritation	Skin Irritation	Sensitization
<b>Sulfur Dioxide</b>	Corrosive, burns	Corrosive, burns	Acute toxicity, Category 3, inhalation; H331: Toxic if inhaled. Skin corrosion, Category 1B; H314: Causes severe skin burns and eye damage.
<b>n-Pentane</b>	Irritation	Irritation	Specific Target Organ Toxicity (single exposure), Category 3; H336: May cause drowsiness or dizziness. Aspiration hazard, Category 1; H304: May be fatal if swallowed and enters airways.
<b>Carbon Monoxide</b>	No information on significant adverse effects	No information on significant adverse effects	Acute toxicity, Category 3, inhalation; H331: Toxic if inhaled. Reproductive toxicity, Category 1A; H360D: May damage the unborn child. Specific Target Organ Toxicity (repeated exposure), Category 1; H372: Causes damage to organs through prolonged or repeated exposure.
<b>Oxygen</b>	No information on significant adverse effects	No information on significant adverse effects	No significant target effects reported.
<b>Nitrogen</b>	Contact with rapidly expanding gas may cause burns or frostbite	No information on significant adverse effects	Difficulty breathing

### Chronic Effects

	Carcinogenicity	Mutagenicity	Reproductive Effects	Developmental Effects
<b>Sulfur Dioxide</b>	IARC: Human Inadequate Evidence, Animal Limited Evidence, Group 3; ACGIH: A4 -Not Classifiable as a Human Carcinogen	Available.	Available.	No data
<b>n-Pentane</b>	Not available	Not available	Not available	No data
<b>Carbon Monoxide</b>	Not available	Available.	Available.	No data
<b>Oxygen</b>	Not known.	Available.	Available.	No data
<b>Nitrogen</b>	Not hazardous	Not available	Not available	No data

## Section 12: Ecological Information

### Fate and Transport

	Eco toxicity	Persistence / Degradability	Bioaccumulation / Accumulation	Mobility in Environment
<b>Sulfur Dioxide</b>	Fish toxicity: 3000 ug/L 0.667-0.833 hour(s) (Avoidance) Atlantic menhaden ( <i>Brevoortia tyrannus</i> ) Invertebrate toxicity: Not available Algal toxicity: 500 ug/L 6 day(s) (Cellular) Green algae ( <i>Rhizoclonium hieroglyphicum</i> ) Phyto toxicity: Not available Other toxicity: >=150 ug/L NR hour(s) (Biochemical) Duckweed ( <i>Lemna minor</i> )	Not available	Not available	Not available
<b>n-Pentane</b>	Fish toxicity: Not available Invertebrate toxicity: 3000000 ug/L 48 week(s) (Mortality) Pacific oyster ( <i>Crassostrea gigas</i> ) Algal toxicity: 1000 ug/L 8 year(s) EC50 (Photosynthesis) Algae, phytoplankton, algal mat (Algae) Phyto toxicity: Not available Other toxicity: Not available	Not available	Not available	Not available
<b>Carbon Monoxide</b>	Fish toxicity: 75000 ug/L 1 day(s) LC100 (Mortality) Orangespotted sunfish ( <i>Lepomis humilis</i> ) Invertebrate toxicity: Not available Algal toxicity: Not available Phyto toxicity: Not available	Relatively non-persistent in the environment. Highly volatile from water.	Not available	Not expected to leach through the soil or the sediment.

	Other toxicity: Not available			
<b>Oxygen</b>	Fish toxicity: Not available Invertebrate toxicity: Not available Algal toxicity: Not available Phyto toxicity: Not available Other toxicity: Not available	Not available	Low bioaccumulation	Not available
<b>Nitrogen</b>	Fish toxicity: Not available Invertebrate toxicity: Not available Algal toxicity: Not available Phyto toxicity: Not available Other toxicity: Not available	Not available	Not available	Not available

## Section 13: Disposal Considerations

<b>Sulfur Dioxide</b>	Dispose in accordance with all applicable regulations.
<b>n-Pentane</b>	Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): D001.
<b>Carbon Monoxide</b>	Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): D001.
<b>Oxygen</b>	Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): D001.
<b>Nitrogen</b>	Dispose in accordance with all applicable regulations.

## Section 14: Transportation Information

### U.S. DOT 49 CFR 172.101

#### DOT Information For This Mixture

<b>Shipping Name</b>	Compressed gas, n.o.s. (Nitrogen, Oxygen)
<b>UN Number</b>	UN1956
<b>Hazard Class</b>	2.2
<b>Hazard Information</b>	Non-Flammable Gas

#### Individual Component Information

	Proper Shipping Name	ID Number	Hazard Class or Division	Packing Group	Labeling Requirements	Passenger Aircraft or Railcar Quantity Limitations	Cargo Aircraft Only Quantity Limitations	Additional Shipping Description
<b>Sulfur Dioxide</b>	Sulfur dioxide	UN1079	2.3	Not applicable	2.3; 8	Forbidden	Forbidden	Toxic-Inhalation Hazard Zone C
<b>n-Pentane</b>	Pentanes	UN1265	3	II	3	N/A	N/A	N/A
<b>Carbon Monoxide</b>	Carbon monoxide, compressed	UN1016	2.3	Not applicable	2.3; 2.1	Forbidden	25 kg	Toxic-Inhalation Hazard Zone D
<b>Oxygen</b>	Oxygen, compressed	UN1072	2.2	Not available	2.2; 5.1	75 kg or L	150 kg	N/A
<b>Nitrogen</b>	Nitrogen, compressed	UN1066	2.2	Not applicable	2.2	75 kg or L	150 kg	N/A

#### Canadian Transportation of Dangerous Goods

	Shipping Name	UN Number	Class	Packing Group / Risk Group
<b>Sulfur Dioxide</b>	Sulfur dioxide	UN1079	2.3; 8	Not applicable
<b>n-Pentane</b>	Pentanes	UN1265	3	II
<b>Carbon Monoxide</b>	Carbon monoxide, compressed	UN1016	2.3; 2.1	Not applicable
<b>Oxygen</b>	Oxygen, compressed	UN1072	2.2; 5.1	Not applicable
<b>Nitrogen</b>	Nitrogen, compressed	UN1066	2.2	Not applicable



# Section 15: Regulatory Information

## U.S. Regulations

	CERCLA Sections	SARA 355.30	SARA 355.40
<b>Sulfur Dioxide</b>	Not regulated.	500 LBS TPQ	500 LBS RQ
<b>n-Pentane</b>	Not regulated.	Not regulated.	Not regulated.
<b>Carbon Monoxide</b>	Not regulated.	Not regulated.	Not regulated.
<b>Oxygen</b>	Not regulated.	Not regulated.	Not regulated.
<b>Nitrogen</b>	Not regulated.	Not regulated.	Not regulated.

## SARA 370.21

	Acute	Chronic	Fire	Reactive	Sudden Release
<b>Sulfur Dioxide</b>	Yes	Yes	No	No	Yes
<b>n-Pentane</b>	Yes	No	Yes	No	No
<b>Carbon Monoxide</b>	Yes	No	Yes	No	Yes
<b>Oxygen</b>	No	No	Yes	No	Yes
<b>Nitrogen</b>	Yes	No	No	No	Yes

## SARA 372.65

<b>Sulfur Dioxide</b>	Not regulated.
<b>n-Pentane</b>	Not regulated.
<b>Carbon Monoxide</b>	Not regulated.
<b>Oxygen</b>	Not regulated.
<b>Nitrogen</b>	Not regulated.

## OSHA Process Safety

<b>Sulfur Dioxide</b>	1000 LBS TQ
<b>n-Pentane</b>	Not regulated.
<b>Carbon Monoxide</b>	Not regulated.
<b>Oxygen</b>	Not regulated.
<b>Nitrogen</b>	Not regulated.

## State Regulations

	CA Proposition 65
<b>Sulfur Dioxide</b>	WARNING: This product can expose you to chemicals including sulfur dioxide, which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> .
<b>n-Pentane</b>	Not regulated.
<b>Carbon Monoxide</b>	WARNING: This product can expose you to chemicals including Carbon Monoxide, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> .
<b>Oxygen</b>	Not regulated.
<b>Nitrogen</b>	Not regulated.

## Canadian Regulations

	WHMIS Classification
<b>Sulfur Dioxide</b>	AD1
<b>n-Pentane</b>	B2
<b>Carbon Monoxide</b>	A, B1, D1A, D2A.
<b>Oxygen</b>	A,C
<b>Nitrogen</b>	A

## National Inventory Status

	US Inventory (TSCA)	TSCA 12b Export Notification	Canada Inventory (DSL/NDL)
<b>Sulfur Dioxide</b>	Listed on inventory.	Not listed.	Not determined.
<b>n-Pentane</b>	Listed on inventory.	PENTANE CAS NUMBER: 109-66-0 SECTION 4	Listed on inventory.
<b>Carbon Monoxide</b>	Listed on inventory.	Not listed.	Listed on inventory.
<b>Oxygen</b>	Listed on inventory.	Not listed.	Not determined.
<b>Nitrogen</b>	Listed on inventory.	Not listed.	Listed on inventory.

## Section 16: Other Information

	NFPA Rating
<b>Sulfur Dioxide</b>	HEALTH=3 FIRE=0 REACTIVITY=0
<b>n-Pentane</b>	HEALTH=2 FIRE=4 REACTIVITY=0
<b>Carbon Monoxide</b>	HEALTH=2 FIRE=4 REACTIVITY=0
<b>Oxygen</b>	HEALTH=0 FIRE=0 REACTIVITY=0 SPECIAL=OX
<b>Nitrogen</b>	HEALTH=0 FIRE=0 REACTIVITY=0 SPECIAL=SA

0 = minimal hazard, 1 = slight hazard, 2 = moderate hazard, 3 = severe hazard, 4 = extreme hazard