



## Safety Data Sheet

50ppm Hydrogen Sulfide, 50% VOL  
Methane, 2% VOL Oxygen; balance  
Nitrogen

**Ideal Calibrations, LLC**  
2750 Oakwood Blvd.  
Melvindale, MI 48122  
(734) 956-0539  
<http://www.idealcalibrations.com/>

### Section 1: Product and Company Identification

**Ideal Calibrations, LLC**  
2750 Oakwood Blvd.  
Melvindale, MI 48122  
(734) 956-0539  
<http://www.idealcalibrations.com/>

Product Code: 50ppm Hydrogen Sulfide, 50% VOL Methane, 2% VOL Oxygen; balance Nitrogen  
Part Number: 0615

**Synonyms:**

**Recommended Use:** Calibration of gas detection devices

**Usage Restrictions:** Do not use if current date is past expiration date on cylinder

### Section 2: Hazards Identification



**Danger**

**Hazard Classification:**

Flammable (Category 1)  
Gases Under Pressure

**Hazard Statements:**

Contains gas under pressure; may explode if heated  
Extremely flammable gas  
Toxic to aquatic life

**Precautionary Statements**

**Prevention:**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

**Response:**

Eliminate all ignition sources if safe to do so.  
Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

**Storage:**

Protect from sunlight.

Store in well-ventilated place.

## Section 3: Composition/Information on Ingredients

	CAS #	Concentration
Hydrogen Sulfide	7783-06-4	0.005
Methane	74-82-8	50
Oxygen	7782-44-7	2
Nitrogen	7727-37-9	47.995

	Chemical Substance	Chemical Family	Trade Names
Hydrogen Sulfide	HYDROGEN SULFIDE	Inorganic gases	HYDROGEN SULFIDE (H2S); DIHYDROGEN MONOSULFIDE; DIHYDROGEN SULFIDE; HYDROSULFURIC ACID; SULFUR DIHYDRIDE; SULFURETED HYDROGEN; SULFUR HYDRIDE; STINK DAMP; SEWER GAS; RCRA U135; UN 1053; H2S
Methane	METHANE, COMPRESSED GAS	Hydrocarbons, Aliphatic, Saturated	FIRE DAMP; MARSH GAS; METHYL HYDRIDE; NATURAL GAS; METHANE; UN 1971; R50; CH4
Oxygen	OXYGEN, COMPRESSED GAS	Inorganic gases	OXYGEN; DIOXYGEN; MOLECULAR OXYGEN; OXYGEN MOLECULE; PURE OXYGEN; UN 1072; O2
Nitrogen	NITROGEN, COMPRESSED GAS	Inorganic gases	DIATOMIC NITROGEN; DINITROGEN; NITROGEN; NITROGEN-14; NITROGEN GAS; UN 1066; N2

## Section 4: First Aid Measures

	Skin Contact	Eye Contact	Ingestion	Inhalation	Note to Physicians
Hydrogen Sulfide	Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.	Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.	If a large amount is swallowed, get medical attention.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.	For inhalation, consider oxygen.
Methane	Wash exposed skin with soap and water.	Flush eyes with plenty of water.	If a large amount is swallowed, get medical attention.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.	For inhalation, consider oxygen.
Oxygen	None expected	None expected	Not likely route of exposure	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. Get immediate medical attention.	None
Nitrogen	Wash exposed skin with soap and water.	Flush eyes with plenty of water.	If a large amount is swallowed, get medical attention.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.	For inhalation, consider oxygen.

## Section 5: Fire Fighting Measures

	Suitable Extinguishing Media	Products of Combustion	Protection of Firefighters
<b>Hydrogen Sulfide</b>	Let burn unless leak can be stopped immediately. Large fires: Use regular foam or flood with fine water spray.	Sulfur oxides	<ul style="list-style-type: none"> <li>Any self-contained breathing apparatus with a full facepiece.</li> <li>Protective material types: butyl rubber, polyvinyl chloride (PVC), neoprene</li> </ul>
<b>Methane</b>	Carbon dioxide, regular dry chemical Large fires: Use regular foam or flood with fine water spray.	Carbon monoxide, carbon dioxide, water	<ul style="list-style-type: none"> <li>Respiratory protection may be needed for frequent or heavy exposure. Any self-contained breathing apparatus with a full facepiece.</li> <li>Respiratory protection may be needed for frequent or heavy exposure. Any self-contained breathing apparatus with a full facepiece.</li> </ul>
<b>Oxygen</b>	Non-flammable. Use extinguishing agent appropriate for the material which is burning. Use water in large quantities for fires involving oxygen.	Oxides of burning material	<ul style="list-style-type: none"> <li>Respiratory protection may be needed for frequent or heavy exposure.</li> <li>None</li> </ul>
<b>Nitrogen</b>	Non-flammable. Use suitable extinguishing media for surrounding fire. Cylinders may rupture or explode if exposed to heat.	Non-flammable	<ul style="list-style-type: none"> <li>Respiratory protection may be needed for frequent or heavy exposure.</li> </ul>

## Section 6: Accidental Release Measures

	Personal Precautions	Environmental Precautions	Methods for Containment
<b>Hydrogen Sulfide</b>	Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas. Ventilate closed spaces before entering. Evacuation radius: 150 feet. For tank, rail car or tank truck: 800 meters (1/2 mile). Do not touch spilled material.	Avoid heat, flames, sparks and other sources of ignition.	Stop leak if possible without personal risk. Remove sources of ignition. Reduce vapors with water spray. Do not get water directly on material.
<b>Methane</b>	Keep unnecessary people away, isolate hazard area and deny entry. Ventilate closed spaces before entering.	Avoid heat, flames, sparks and other sources of ignition.	Stop leak if possible without personal risk. Reduce vapors with water spray. Remove sources of ignition.
<b>Oxygen</b>	Keep unnecessary people away, isolate hazard area and deny entry. Ventilate closed spaces before entering.	Avoid contact with combustible materials.	Stop leak if possible without personal risk.
<b>Nitrogen</b>	Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas.	No significant effects from contamination expected.	Stop leak if possible without personal risk.

	Methods for Cleanup	Other Information
<b>Hydrogen Sulfide</b>	Collect runoff for disposal as potential hazardous waste. Dike for later disposal. Absorb with sand or other non-combustible material. Add an alkaline material (lime, crushed limestone, sodium bicarbonate, or soda ash).	Notify Local Emergency Planning Committee and State Emergency Response Commission for release greater than or equal to RQ (U.S. SARA Section 304). If release occurs in the U.S. and is reportable under CERCLA Section 103, notify the National Response Center at (800)424-8802 (USA) or (202)426-2675 (USA).
<b>Methane</b>	Not available	Not available
<b>Oxygen</b>	Stop leak and ventilate	None
<b>Nitrogen</b>	N/A	N/A

## Section 7: Handling and Storage

	Handling	Storage
<b>Hydrogen Sulfide</b>	Store and handle in accordance with all current regulations and standards. Protect from physical damage. Store outside or in a detached building. Store in a cool, dry place. Store in a well-ventilated area. Avoid contact with light. Grounding and bonding required. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101. Notify State Emergency Response Commission for storage or use at amounts greater than or equal to the TPQ (U.S. EPA SARA Section 302). SARA Section 303 requires facilities storing a material with a TPQ to participate in local emergency response planning (U.S. EPA 40 CFR 355.30). Keep separated from incompatible substances.	Subject to handling regulations: U.S. OSHA 29 CFR 1910.119.

	Handling	Storage
<b>Methane</b>	Store and handle in accordance with all current regulations and standards. Grounding and bonding required. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101.	Keep separated from incompatible substances.
<b>Oxygen</b>	Store and handle in accordance with all current regulations and standards. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101.	Keep separated from incompatible substances.
<b>Nitrogen</b>	Store and handle in accordance with all current regulations and standards. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101.	Keep separated from incompatible substances.

## Section 8: Exposure Controls/Personal Protection

	Exposure Guidelines
<b>Hydrogen Sulfide</b>	HYDROGEN SULFIDE: 20 ppm OSHA ceiling 50 ppm OSHA peak 10 minute(s) (once if no other measurable exposure occurs) 10 ppm (14 mg/m3) OSHA TWA (vacated by 58 FR 35338, June 30, 1993) 15 ppm (21 mg/m3) OSHA STEL (vacated by 58 FR 35338, June 30, 1993) 10 ppm ACGIH TWA 15 ppm ACGIH STEL 10 ppm (15 mg/m3) NIOSH recommended ceiling 10 minute(s) TLV-TWA: 1ppm Upper respiratory irritation (ACGIH)
<b>Methane</b>	METHANE, COMPRESSED GAS: ALIPHATIC HYDROCARBON GASES ALKANE (C1-C4): 1000 ppm ACGIH TWA METHANE: No occupational exposure limits established. ALIPHATIC HYDROCARBON GASES ALKANE (C1-C4): 1000 ppm ACGIH TWA
<b>Oxygen</b>	OXYGEN, COMPRESSED GAS: No occupational exposure limits established.
<b>Nitrogen</b>	NITROGEN, COMPRESSED GAS: NITROGEN: ACGIH (simple asphyxiant)

### Engineering Controls

Handle only in fully enclosed systems.

	Eye Protection	Skin Protection	Respiratory Protection
<b>Hydrogen Sulfide</b>	Wear splash resistant safety goggles with a face shield. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.	Wear appropriate chemical resistant clothing.	Any self-contained breathing apparatus with a full facepiece.
<b>Methane</b>	Eye protection not required, but recommended.	Protective clothing is not required.	Respiratory protection may be needed for frequent or heavy exposure. Any self-contained breathing apparatus with a full facepiece.
<b>Oxygen</b>	Eye protection not required, but recommended.	Protective clothing is not required.	Respiratory protection may be needed for frequent or heavy exposure.
<b>Nitrogen</b>	Eye protection not required, but recommended.	Protective clothing is not required.	Respiratory protection may be needed for frequent or heavy exposure.

### General Hygiene considerations

- Avoid breathing vapor or mist
- Avoid contact with eyes and skin
- Wash thoroughly after handling and before eating or drinking

## Section 9: Physical and Chemical Properties

	Physical State	Appearance	Color	Change in Appearance	Physical Form	Odor	Taste
<b>Hydrogen Sulfide</b>	Gas	Colorless	Colorless	N/A	Gas	Rotten egg odor	N/A
<b>Methane</b>	Gas	Colorless	Colorless	N/A	Gas	Odorless	Tasteless
<b>Oxygen</b>	Gas	Clear	Colorless	N/A	Gas	Odorless	Tasteless
<b>Nitrogen</b>	Gas	Clear	Colorless	N/A	Gas	Odorless	Tasteless

	Flash Point	Flammability	Partition Coefficient	Autoignition Temperature	Upper Explosive Limits	Lower Explosive Limits
<b>Hydrogen Sulfide</b>	Flammable	Not available	Not available	500 F (260 C)	45.5%	3.9%
<b>Methane</b>	-369 F (-223 C)	Not available	724.44 (log = 2.87) (estimated from water solubility)	999 F (537 C)	15%	5%
<b>Oxygen</b>	Not flammable	Not available	Not available	Nonflammable	Nonflammable	Nonflammable
<b>Nitrogen</b>	Not flammable	Not available	Not available	Nonflammable	Nonflammable	Nonflammable

	Boiling Point	Freezing Point	Vapor Pressure	Vapor Density	Specific Gravity	Water Solubility	pH	Odor Threshold	Evaporation Rate	Viscosity
<b>Hydrogen Sulfide</b>	-78 to -77 F (-61 to -60.3 C)	-123 F (-86 C)	15200 mmHg @ 25 C	1.2 (Air=1)	1.192	2.58-2.9% @ 20 C	4.5-<7 (saturated solution)	0.13 ppm	Not applicable	0.0128 cP @ 25 C
<b>Methane</b>	-260 F (-162 C)	-297 F (-183 C)	760 mmHg @ -161 C	0.555 (Air=1)	Not applicable	3.5% @ 17 C	Not applicable	Not available	Not applicable	0.01118 cP @ 27 C
<b>Oxygen</b>	-297 F (-183 C)	-360 F (-218 C)	760 mmHg @ -183 C	1.1 (Air=1)	Not applicable	3.2% @ 25 C	Not applicable	Not available	Not applicable	0.02075 cP @ 25 C
<b>Nitrogen</b>	-321 F (-196 C)	-346 F (-210 C)	760 mmHg @ -196 C	0.967 (Air=1)	Not applicable	1.6% @ 20 C	Not applicable	Not available	Not applicable	0.01787 cP @ 27 C

	Molecular Weight	Molecular Formula	Density	Weight per Gallon	Volatility by Volume	Volatility	Solvent Solubility
<b>Hydrogen Sulfide</b>	34.08	H2-S	1.539 g/L @ 0 C	Not available	Not available	Not applicable	Soluble: Carbon disulfide, alcohol, ether, glycerol, gasolines, kerosene, crude oil, alkali solutions
<b>Methane</b>	16.04	C-H4	0.717 g/L @ 0 C	Not available	Not applicable	Not applicable	Soluble: Alcohol, ether, benzene, organic solvents
<b>Oxygen</b>	31.9988	O2	1.309 g/L @ 25 C	Not available	Not applicable	Not applicable	Soluble: Alcohol
<b>Nitrogen</b>	28.0134	N2	1.2506 g/L	Not available	100%	1	Soluble: Liquid ammonia

## Section 10: Stability and Reactivity

	Stability	Conditions to Avoid	Incompatible Materials
<b>Hydrogen Sulfide</b>	Stable at normal temperatures and pressure.	Stable at normal temperatures and pressure.	Combustible materials, metals, oxidizing materials, halogens, metal oxides, metal salts, bases, rust, oxidants, oxygen, copper powder, acetaldehyde, silver fulminate
<b>Methane</b>	Stable at normal temperatures and pressure.	Stable at normal temperatures and pressure.	Halogens, oxidizing materials, combustible materials
<b>Oxygen</b>	Stable at normal temperatures and pressure.	Stable at normal temperatures and pressure.	Combustible materials, halo carbons, metals, bases, reducing agents, amines, metal salts, oxidizing materials, alkaline earth and alkali metals
<b>Nitrogen</b>	Stable at normal temperatures and pressure.	Stable at normal temperatures and pressure.	Metals, oxidizing materials

	Hazardous Decomposition Products	Possibility of Hazardous Reactions
<b>Hydrogen Sulfide</b>	Oxides of sulfur	Will not polymerize.
<b>Methane</b>	Oxides of carbon	Will not polymerize.
<b>Oxygen</b>	Miscellaneous decomposition products	Will not polymerize.
<b>Nitrogen</b>	Oxides of nitrogen	Will not polymerize.

## Section 11: Toxicology Information

### Acute Effects

	Oral LD50	Dermal LD50	Inhalation
<b>Hydrogen Sulfide</b>	444 ppm inhalation-rat LC50	Irritation 0.000125 ppm/5 hour(s) eyes-human	Irritation, lack of sense of smell, sensitivity to light, nausea, vomiting, difficulty breathing, headache, drowsiness, dizziness, disorientation, tremors, visual disturbances, suffocation, lung congestion, internal bleeding, heart damage, nerve damage, brain damage, coma, death
<b>Methane</b>	Not available	Not available	Nausea, vomiting, difficulty breathing, irregular heartbeat, headache, drowsiness, fatigue, dizziness, disorientation, mood swings, tingling sensation, loss of coordination, suffocation, convulsions, unconsciousness, coma

	Oral LD50	Dermal LD50	Inhalation
<b>Oxygen</b>	Not established	Not established	Irritation, changes in body temperature, nausea, difficulty breathing, irregular heartbeat, dizziness, disorientation, hallucinations, mood swings, pain in extremities, tremors, lung congestion, convulsions
<b>Nitrogen</b>	Not available	Not available	Nausea, vomiting, difficulty breathing, headache, drowsiness, dizziness, tingling sensation, loss of coordination, convulsions, coma

	Eye Irritation	Skin Irritation	Sensitization
<b>Hydrogen Sulfide</b>	Irritation, sensitivity to light, visual disturbances	Irritation liquid: frostbite	Acute toxicity, Category 2, inhalation; H330: Fatal if inhaled. Specific Target Organ Toxicity (single exposure), Category 3; H335: May cause respiratory irritation. Hazardous to the aquatic environment, Acute Category 1; H400: Very toxic to aquatic life
<b>Methane</b>	No information on significant adverse effects	No information on significant adverse effects	Difficulty breathing
<b>Oxygen</b>	No information on significant adverse effects	No information on significant adverse effects	No significant target effects reported.
<b>Nitrogen</b>	Contact with rapidly expanding gas may cause burns or frostbite	No information on significant adverse effects	Difficulty breathing

### Chronic Effects

	Carcinogenicity	Mutagenicity	Reproductive Effects	Developmental Effects
<b>Hydrogen Sulfide</b>	Not available	Not available	Available.	No data
<b>Methane</b>	Not available	Not available	Not available	No data
<b>Oxygen</b>	Not known.	Available.	Available.	No data
<b>Nitrogen</b>	Not hazardous	Not available	Not available	No data

## Section 12: Ecological Information

### Fate and Transport

	Eco toxicity	Persistence / Degradability	Bioaccumulation / Accumulation	Mobility in Environment
<b>Hydrogen Sulfide</b>	Fish toxicity: Acute LC50 7 ug/L Fresh water Fish - Fathead minnow - Pimephales promelas - FRY 96 hours; 14.9 ug/L 96 hour(s) LC50 (Mortality) Fathead minnow (Pimeph Invertebrate toxicity: 9730 ug/L 1.5 hour(s) (Mortality) Mediterranean mussel (Mytilus galloprovincialis) Algal toxicity: Not available Phyto toxicity: Not available Other toxicity: Not available	Highly toxic to aquatic life.	Not available	Not available
<b>Methane</b>	Fish toxicity: Not available Invertebrate toxicity: Not available Algal toxicity: Not available Phyto toxicity: Not available Other toxicity: Not available	Relatively non-persistent in the environment. Moderately volatile from water.	Accumulates very little in the bodies of living organisms.	Not expected to leach through the soil or the sediment.
<b>Oxygen</b>	Fish toxicity: Not available Invertebrate toxicity: Not available Algal toxicity: Not available Phyto toxicity: Not available Other toxicity: Not available	Not available	Low bioaccumulation	Not available
<b>Nitrogen</b>	Fish toxicity: Not available Invertebrate toxicity: Not available Algal toxicity: Not available Phyto toxicity: Not available Other toxicity: Not available	Not available	Not available	Not available

## Section 13: Disposal Considerations

<b>Hydrogen</b>	Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous
-----------------	--

<b>Sulfide</b>	Waste Number(s): U135.
<b>Methane</b>	Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): D001.
<b>Oxygen</b>	Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): D001.
<b>Nitrogen</b>	Dispose in accordance with all applicable regulations.

## Section 14: Transportation Information

### U.S. DOT 49 CFR 172.101

#### DOT Information For This Mixture

<b>Shipping Name</b>	Compressed gas, flammable, n.o.s. (Methane, Nitrogen)
<b>UN Number</b>	UN1954
<b>Hazard Class</b>	2.1
<b>Hazard Information</b>	FLAMMABLE GAS

#### Individual Component Information

	Proper Shipping Name	ID Number	Hazard Class or Division	Packing Group	Labeling Requirements	Passenger Aircraft or Railcar Quantity Limitations	Cargo Aircraft Only Quantity Limitations	Additional Shipping Description
<b>Hydrogen Sulfide</b>	Hydrogen sulfide	UN1053	2.3	Not applicable	2.3; 2.1	Forbidden	Forbidden	Toxic-Inhalation Hazard Zone B
<b>Methane</b>	Methane, compressed	UN1971	2.1	Not applicable	2.1	Forbidden	150 kg	N/A
<b>Oxygen</b>	Oxygen, compressed	UN1072	2.2	Not available	2.2; 5.1	75 kg or L	150 kg	N/A
<b>Nitrogen</b>	Nitrogen, compressed	UN1066	2.2	Not applicable	2.2	75 kg or L	150 kg	N/A

#### Canadian Transportation of Dangerous Goods

	Shipping Name	UN Number	Class	Packing Group / Risk Group
<b>Hydrogen Sulfide</b>	HYDROGEN SULFIDE; or HYDROGEN SULPHIDE	UN1053	2.3; 2.1	Not applicable
<b>Methane</b>	Methane, compressed	UN1971	2.1	Not applicable
<b>Oxygen</b>	Oxygen, compressed	UN1072	2.2; 5.1	Not applicable
<b>Nitrogen</b>	Nitrogen, compressed	UN1066	2.2	Not applicable

## Section 15: Regulatory Information

### U.S. Regulations

	CERCLA Sections	SARA 355.30	SARA 355.40
<b>Hydrogen Sulfide</b>	100 LBS RQ	500 LBS TPQ	100 LBS RQ
<b>Methane</b>	Not regulated.	Not regulated.	Not regulated.
<b>Oxygen</b>	Not regulated.	Not regulated.	Not regulated.
<b>Nitrogen</b>	Not regulated.	Not regulated.	Not regulated.

### SARA 370.21

	Acute	Chronic	Fire	Reactive	Sudden Release
<b>Hydrogen Sulfide</b>	Yes	No	Yes	No	Yes
<b>Methane</b>	Yes	No	Yes	No	Yes
<b>Oxygen</b>	No	No	Yes	No	Yes
<b>Nitrogen</b>	Yes	No	No	No	Yes

### SARA 372.65

<b>Hydrogen Sulfide</b>	HYDROGEN SULFIDE: Administrative stay issued Aug. 22, 1994
-------------------------	--

<b>Methane</b>	Not regulated.
<b>Oxygen</b>	Not regulated.
<b>Nitrogen</b>	Not regulated.

### OSHA Process Safety

<b>Hydrogen Sulfide</b>	1500 LBS TQ
<b>Methane</b>	Not regulated.
<b>Oxygen</b>	Not regulated.
<b>Nitrogen</b>	Not regulated.

### State Regulations

	<b>CA Proposition 65</b>
<b>Hydrogen Sulfide</b>	Not regulated.
<b>Methane</b>	Not regulated.
<b>Oxygen</b>	Not regulated.
<b>Nitrogen</b>	Not regulated.

### Canadian Regulations

	<b>WHMIS Classification</b>
<b>Hydrogen Sulfide</b>	A, B1, D1A, D2B.
<b>Methane</b>	A, B1
<b>Oxygen</b>	A,C
<b>Nitrogen</b>	A

### National Inventory Status

	<b>US Inventory (TSCA)</b>	<b>TSCA 12b Export Notification</b>	<b>Canada Inventory (DSL/NDSL)</b>
<b>Hydrogen Sulfide</b>	Listed on inventory.	Not listed.	Listed on inventory.
<b>Methane</b>	Listed on inventory.	Not listed.	Listed on inventory.
<b>Oxygen</b>	Listed on inventory.	Not listed.	Not determined.
<b>Nitrogen</b>	Listed on inventory.	Not listed.	Listed on inventory.

## Section 16: Other Information

	<b>NFPA Rating</b>
<b>Hydrogen Sulfide</b>	HEALTH=4 FIRE=4 REACTIVITY=0
<b>Methane</b>	HEALTH=0 FIRE=4 REACTIVITY=0
<b>Oxygen</b>	HEALTH=0 FIRE=0 REACTIVITY=0 SPECIAL=OX
<b>Nitrogen</b>	HEALTH=0 FIRE=0 REACTIVITY=0 SPECIAL=SA

0 = minimal hazard, 1 = slight hazard, 2 = moderate hazard, 3 = severe hazard, 4 = extreme hazard